

103 TROWEL MASTIC

Colour	Product Code	Pack Size	Box Qty
Red	TROW6RD	6KG	2
Stone	TROW6ST	6KG	2
Red	TROWRD	3KG	4
Stone	TROWST	3KG	4

Product Description

EVERBUILD TROWEL MASTIC is premium oil based mastic for perimeter pointing around wood and metal window and doorframes. Trowel applied. Forms a weather-tight seal. Also suitable for re-pointing brickwork and for bedding windows or doorframes into their surrounds.

Benefits

- Easier to apply than most competitive mastics.
- Extended shelf life.
- Added plasticiser (polybutene) improves adhesion and helps prevent cracking.

Areas For Use

- Pointing around/bedding in windows and door frames.
- Pointing brickwork.

Limitations

- Unsuitable for plastic frames heat absorbing glass.

Surface Preparation

All surfaces must be clean, dry, free from dust, grease and other contamination.

Application

Apply using a thin pointing trowel or putty knife, working well into the joint and ensuring no voids remain. Finish smooth to a triangular fillet. When used for fillet pointing between frame and surround, joints should be a minimum width of 10mm with a minimum depth of 6mm.

OVERPAINTING AND MAINTENANCE

Product may be fully protected with an undercoat and top coat after a surface skin has formed; i.e. after 7 -28 days. This will prolong the working life, but is not essential. Make good any defects on an annual basis.

Specific Data

Appearance	Thick buff or red paste.
Specific Gravity @ 20°C	2.0 gcm ³ (approx)
Movement Accommodation	Low (5% total)
Oil Content	10% min
Application Temperature	5°C to 40°C.
Service Temperature	-20 to 50°C.
Service Life	Up to 15 years when applied according to the manufacturers directions.
Coverage	For facing, usage will be approximately 15 linear metres per kg for a triangular fillet with a 10mm face section.

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store at moderate temperatures in original containers. Any surface oil will blend in after mixing by hand.

Shelf Life

9 months from date of manufacture when stored according to manufacturers instructions.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.